

8-Port Gigabit Ethernet Switch

Model: S108GS



Product Introduction

This switch is a Gigabit Ethernet Switch designed specifically for small to medium-sized network environments. It provides 8 adaptive 10/100/1000Mbps RJ45 ports, all of which support automatic cross/parallel twisted-pair cable detection (Auto MDI/MDIX). Each port can provide a maximum bidirectional transmission rate of 2Gbps. It is easy to install and maintain, and is an ideal choice for building small to medium-sized enterprise networks.

Features

- ◎ 8 10/100/1000Base-TX ports
- ◎ Supports a 4K MAC address table
- ◎ Supports 9K Jumbo frame
- ◎ Build-in 1.5Mbit cache space
- ◎ All ports support 10/100/1000Mbps speed auto-negotiation
- ◎ Support Smart DIP Switch, to reach 3mode: Extend 250meter&Port Vlan(Port Isolation)&QoS
- ◎ All ports support half/full duplex auto-negotiation and automatic MDI/MDI-X function
- ◎ All ports support line-speed forwarding for smoother transmission
- ◎ Supports desktop and wall-mount installation
- ◎ Plug-and-play operation, easy to use without any configuration

Specification

Model	S108GS
I/O Interface	
Power	DC 5-12V
Ethernet	8*RJ45 10/100/1000Mbps Ports
Features	<p>With the DIP switch, support 3modes:</p> <p>E: AI Extend 250meters transmission;</p> <p>V: Turn on, 1-4 Port support each port Isolation & VLAN.</p> <p>Q: Qos</p>
Performance	
Switching Capacity	16Gbps
Packet Forwarding Rate	7.44Mpps@64byte
Packet Buffer	1.51Mb
MAC Address	4K
Jumbo Frame	9216b
Transfer Mode	Store-and-forward (full wire-speed)
MTBF	100000 hour
Standard	
Network protocol	IEEE802.3 10Base-T
	IEEE802.3u 100Base-TX
	IEEE802.3ab 1000Base-T
	IEEE 802.1p tagged frames
	IEEE802.1W Spanning Tree
Industry Standard	IEEE 802.3x flow control
	EMI: FCC Part 15 CISPR (EN55032) class A
	EMS: EN61000-4-2 (ESD)
Network Medium	EN61000-4-5(Surge)
	10Base-T : Cat3,4,5 or above UTP(≤100m)
	100Base-TX : Cat5 or above UTP(≤100m)
Environment	1000Base-TX : Cat5 or aboveUTP(≤100m)
	Working Temperature: -10~50° C
	Working Environment
	Storage Temperature: -40~70° C
Indication	Working Humidity : 10%-90%, non-condensing
	Storage Temperature: 5%-90%, non-condensing
	LED Indicators
	PWR (Power indicator) 、Link/Act (Network Link)

Mechanical	
Structure Size	Product Size: 141 × 79 × 28mm
	Product Net-Weight: 280g
Certification	
Certification	CE, FCC, RoHS,
Package Contents	
Switch	1 pcs
Power cord	1 pcs
Quick installation guide	1 pcs



HIMAX



HIMAX TECHNOLOGY LIMITED

www.himax-technology.com

Email: sales@himax-technology.com

F10, Fuhong Building, No.120 Yongfu Road, Qiaotou Community Fuhai Street, BaoanDistrict, Shenzhen China



Company Website

© 2024 himax-technology.com. All Rights Reserved.
Version, V1.0, updated 202401

The information in this document is subject to change without notice.

Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.